AMENDMENTS TO THE CLAIMS

- 1. 17. (Cancelled)
- 18. (Currently Amended) A corner and bulkhead protector for a cargo carrying vehicle comprising;
 - a first cargo engaging surface;
 - a second cargo engaging surface;
 - said first cargo engaging surface adapted to engage a front face of an item of cargo;
 - said second cargo engaging surface adapted to engage a side of an item of cargo;
 - a first strap engaging surface;
 - a second strap engaging surface;
- said first strap engaging surface being opposite said first cargo engaging surface, defining a first wall therebetween;
- said second strap engaging surface being opposite said second cargo engaging surface, and defining a second wall therebetween;
 - a first strap supporting surface;
 - a second strap supporting surface;
- said first strap supporting surface extending substantially perpendicularly outwardly from said first wall;
- said second strap engaging surface being opposite said second cargo engaging surface[[,]] and extending substantially perpendicularly outwardly from said second wall;
- said first and second strap supporting surfaces forming a continuous and coplanar strap support member;
- first and second vertical webs extending upward from said first and second strap supporting surfaces in planes perpendicular to said walls;

first and second horizontal webs extending inward from said first and second vertical webs in a plane perpendicular to said strap support member;

said a combination of ones of said walls, supporting surfaces, and webs forming a first corrugation;

a second corrugation corresponding in form to said first corrugation, formed and arranged to extend said protector over a selected portion of a corner of a cargo;

said corrugations providing for both increased strength and rigidity and providing support for load restraining web straps.

19. (Currently Amended) The <u>corner and bulkhead</u> protector of claim 18, further comprising:

said supporting surfaces, horizontal webs and walls formed and arranged to provide a corrugation at least 3" deep; and at least 7" wide.

20. (Currently Amended) The <u>corner and bulkhead</u> protector of claim 19 wherein said corner <u>and bulkhead</u> protector is made of high molecular weight high density polyethylene.